

## Specifiche Containers

Ecco le caratteristiche e le dimensioni interne indicative dei principali tipi di containers



### DRY BOX

Tipo	Peso		Capacita'	Dimensioni est. (mm)			Dimensioni int. (mm)			Apertura Porta	
	Payload kg	Tara		Cbm	Lung.	Larg.	Alt.	Lung.	Larg.	Alt.	Larg.
20'DC	21700-28240	2210-2400	33.3	6058	2438	2591	5900	2345	2400	2335	2290
40'DC	26740-26850	3630-3740	67.7	12192	2438	2591	12030	2345	2400	2335	2290
40'HC	26580-26600	3880-3900	76.5	12192	2438	2896	12030	2350	2690	2335	2595



### FLAT RACK

Tipo	Peso		Capacita'	Dimensioni est. (mm)			Dimensioni int. (mm)			Piano di Carico	
	Payload kg	Tara		Cbm	Lung.	Larg.	Alt.	Lung.	Larg.	Alt.	Lung. Laterale
20'FR	17859-30150	2350-2500		6058	2438	2591	5900	2400	2270-2285	5530-5700	2230-2250
40'FR	40100	4900		12192	2438	2591	12150	2400	2035	11835	2230-2240



### OPEN TOP

Tipo	Peso		Capacita'	Dimensioni est. (mm)			Dimensioni int. (mm)			Apertura Porta		Apertura Tetto	
	Payload kg	Tara		Cbm	Lung.	Larg.	Alt.	Lung.	Larg.	Alt.	Larg.	Alt.	Lung.
20'OT	21770-28230	2230-2250	31.8-32.9	6058	2438	2591	5900	2330-2340	2380	2330	2220-2250	5540-5760	2190-2210
40'OT	26830	3650	67.1	12192	2438	2591	12045	2340	2380	2235	2255	11890	2185-2210



### REEFER CONTAINER (temperatura controllata -25/+25°C)

Tipo	Peso		Capacita'	Dimensioni est. (mm)			Dimensioni int. (mm)			Apertura Porta		Vtaggio/Hz
	Payload kg	Tara		Cbm	Lung.	Larg.	Alt.	Lung.	Larg.	Alt.	Larg.	
20'RC	17090-27280	2850-3500	26.2-28.3	6058	2438	2591	5480-5500	2230-2285	2135-2255	2165-2285	2160-2210	180-220V & 380-440V, 50/60Hz

40'RC	25080-25980	4500-5400	57.5-58.7	12192	2438	2591	11235 - 11575	2240-2285	2175-2250	2240-2280	2200	380/440V, 50/60Hz
40'HR	25780-29250	4700-5200	66.7-68	12192	2438	2895	11575	2280-2550	2525-2550	2280-2290	2435	1380/440V, 50/60Hz



## VENTILATED CONTAINER

Tipo	Peso		Capacita'	Dimensioni est. (mm)			Dimensioni int. (mm)			Apertura Porta	
	Payload kg	Tara	Cbm	Lung.	Larg.	Alt.	Lung.	Larg.	Alt.	Larg.	Alt.
20'RC	21350-27000	2160-2780	32.2-33.8	6058	2438	2591	5885-5935	2330-2370	2375-2410	2285-2335	2260-2290



## TANK CONTAINER

Tipo	Peso		Capacita'	Dimensioni est. (mm)		
	Payload kg	Tara	Litri	Lung.	Larg.	Alt.
20'RC	30480	3159	24000	6058	2438	2591



## COLLAPSIBLE CONTAINER

Tipo	Peso		Capacita'	Dimensioni est. (mm)		
	Payload kg	Tara	Lung.	Larg.	Alt.	
20'DC	27722	2749	5630	2200	2230	
40'DC	38918	5800	12060	2080	1950	



## HARD TOP

Tipo	Peso		Capacita'	Dimensioni est. (mm)			Dimensioni int. (mm)			Apertura Porta	
	Payload kg	Tara	Cbm	Lung.	Larg.	Alt.	Lung.	Larg.	Alt.	Larg.	Alt.
20'	27890	2590	32,8	x	x	x	5886	2342	2375	2336	2280
40'	25780	4700	67,2	x	x	x	12020	2342	2388	2336	1896
40'HC	25780	4700	75,8	x	x	x	12020	2342	2693	2336	1896